



## Product Data

# Performance Biolubes BioHydraulic 32

Bio-Based Hydraulic Oil

## Description

Castrol *Performance Biolubes BioHydraulic 32* is a sustainable bio-based hydraulic oil formulated with optimized plant-based oils that surpass the lubricity of the most conventional oils. It protects against wear and has high flash points for safety.

## Applications

- All metalworking related hydraulic systems requiring ISO 32 oils.
- Not formulated for cold temperature use. Should be stored inside at all time.

## Advantages

- Stable performance through a wide operating temperature range
- Good seal compatibility
- High flash and fire points
- Made from North America-grown plant-based oils
- Superior thin-film protection to reduce wear
- Protect all metal components from rust and corrosion

## Typical Properties

	<u>Value</u>	<u>Test Method</u>
Appearance	Light Yellow	Visual
Viscosity @40°C, cSt	40	ASTM D 445
Viscosity @100°C, cSt	8.5	ASTM D 445
Flash Point, °C (°F)	310 (590)	ASTM D 92
Fire Point, °C (°F)	348 (658)	ASTM D 92
4-Ball Wear, mm	0.30	ASTM D 4172
Pin & Vee Block Test	>4500 lbs	ASTM D 3233A
Pour Point, °C (°F)	-20 (-4)	ASTM D 97
Non Staining	1b	ASTM 130-56

Castrol Performance Biolubes Bio Hydraulic 32  
26 Jun 2012

Castrol and the Castrol logo are trademarks of Castrol Limited, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.